


NANOWAVE SYNTHETIC FILTER MEDIA



NanoWave®

H&V, a globally recognized leader in high-performance filtration media, has developed a new air filtration solution that exceeds traditional synthetic media standards. New NanoWave technology delivers enhanced efficiency in a wide range of industries.



**Hollingsworth
& Vose**

For years, the filtration industry has been looking for a synthetic alternative to glass mat media that offers better filter performance with lower energy costs. To meet this challenge, Hollingsworth & Vose Company has developed a unique, environmentally friendly choice for air filtration that meets the standards for HVAC bag applications.

NanoWave®, H&V's proprietary extended surface synthetic media, offers the same efficiency and resistance in an uncharged state as glass mat media. However, NanoWave synthetic media eliminates the occurrence of fiber shedding that is associated with glass media during filter processing, installation, and use.

Designed specifically to meet ASHRAE 52.2 and new EN779 standards, NanoWave can be converted into a filter using conventional bag manufacturing equipment, eliminating capital expenses for plant equipment switching costs.

NanoWave is currently being used in applications that include the following:

- Commercial HVAC systems
- Aircraft paint spray facilities

Other potential NanoWave applications include

- Residential HVAC systems
- Vacuum cleaner bag and exhaust filters
- Respirator filter media
- Auto cabin air filter media

NanoWave filters last longer than conventional glass media, and this high-loft media offers twice the dust-holding capabilities of traditional synthetic media, resulting in a more efficient and economic filter.

Additionally, NanoWave's high stiffness and updated design allow proper bag opening, and the material retains its shape in variable HVAC systems, reducing setup time and increasing productivity.

Benefits

- Increased filter life
- Excellent dust-holding capacity
- Reduced disposal cost
- Elimination of fiber shedding
- Lower energy costs through better air handling
- Processing on conventional and ultrasonic equipment



H&V's innovative NanoWave synthetic media improves filtration effectiveness and productivity compared to traditional synthetics.



Performance efficiency and resistance

Compared to conventional synthetic media, which relies on electrostatic charge, NanoWave meets the same efficiency at half the resistance in a discharged condition.

NanoWave can be offered as either a charged or uncharged media. Charged media offers the advantage of enhanced initial efficiency on submicron particles.

Discharged efficiency vs. pressure drop

NanoWave offers much lower pressure drop for a given efficiency versus standard synthetic, resulting in lower energy consumption for air handling equipment.



www.hollingsworth-vose.com

Hollingsworth & Vose Company
112 Washington Street
East Walpole, MA 02032 USA
508-850-2000

Hollingsworth & Vose Europe
Friedberger Strasse 191
D-61118 Bad Vilbel, Germany
Tel +49 (0) 6101 98167-00
Fax +49 (0) 6101 98167-20

Hollingsworth & Vose (Suzhou)
Company, Ltd.
No. 39 Song Bei Road
Suzhou Industrial Park,
Jiangsu, China 215126
Tel (+86) 512-6767 8600
Fax (+86) 512-6767 8652

The H&V logo, HVision, and NanoWave are registered trademarks of Hollingsworth & Vose Company. All other marks are trademarks of their respective companies.

© 2011 Hollingsworth & Vose. All rights reserved.

10/11 Printed in USA 1121025

NanoWave pressure drop for various classifications

	Filtration Classification	Pressure Drop (Pa @ 0.11 m/s)
European Standards	F6	23
	F7	37
	F8	79
U.S. Standards	MERV 11	23
	MERV 14	65
	MERV 15	90

Please note: These are average values and do not form a specification.

