



WA01325M2

Technical Data Sheet

Air Filtration



NanoWave® - HVAC

100% polypropylene media for HVAC applications such as pocket filters.



NanoWave®

		Target	Range	Test Method
CLASSIFICATION(S):	P-MARK			
	US 52.2	MERV 13		
	EN779 : 2012			
BASIS WEIGHT:	(g/m ²)	170	150 - 190	WI-8.2.4-00-01.003
THICKNESS:	(mm)	6.1	4.8 - 7.4	WI-8.2.4-00-01.017
	(mil)	240	190 - 290	
AIRFLOW RESISTANCE:	(Pa)	51	37 - 65	
	(mm WG)	5.2	3.8 - 6.6	TSI 8130 (12.7cm/sec (25 FPM) face velocity)
DOP EFFICIENCY:	(% 0.3 micron DOP)	50	45 - 55	TSI 8130 (12.7 cm/sec (25 FPM) face velocity)
FLAMMABILITY DATA:	DIN 53438	F1		
	DIN4102-1	B2		
	EN 13501	Not tested		
	UL	Not tested		
MAX CONT. OPERATING TEMP.	°C	70		

All product data and statements are indicative of typical properties and characteristics obtainable. This data sheet is to be used as a guide and not as a specification sheet. H&V makes no representation or warranty except as otherwise agreed to in writing between the parties.